



18 Inch Foam Filled Containment Boom
TXB-18-TTC
Drawing Illustrative Only – Not to Scale
Free board : 6 inches
Draft : 12 inches
Section length : 100 feet
Segment per 100' section : 26
Fabric : 22 Oz per Sq Yd Vinyl Coated Polyester PVC
Color : International Orange
Floatation logs : Rolled Closed cell polyethylene foam
Top tension member : 5/16" HDG steel cable
Ballast and bottom tension : 1/4" HDG steel chain
End connectors : ASTM F962-94 universal "Z" connector, fitted with stainless steel toggle pin and lanyard
Water holes per 100' section : 24
Anchor points : 2
Weight per 100' section : 220 pounds
Storage volume per 100' section : 28 ft³
Boom ultimate tensile strength: 20,000+ pounds
Buoyancy to weight ratio : 6.1
Section length options : 50 ft / 100 ft

Boom Configuration
A: Top Tension Pocket
B: Top Tension
C: Cable eye with thimble
D: Shackle
E: ASTM End Connectors
F: One inch RF welds
G: Foam Log
H: Toggle Pin
I: Toggle Pin hole
J: Anchor Point
K: Air and water drainage hole
L: Chain Pocket
M: Ballast Chain



Texas Boom Company
16600 Park Row Drive
Houston, TX 77084
(281) 441-2002
sales@texasboom.com

Rev B: 4/16/2020