



30 Inch Foam Filled Containment Boom
TXB-30-TTC
Drawing Illustrative Only – Not to Scale
Free board : 10 inches
Draft : 20 inches
Section length : 100 feet
Segment per 100' section : 24
Fabric: 22 Oz per Sq Yd Vinyl Coated Polyester PVC
Color : International Orange
Floatation logs : Rolled Closed cell polyethylene foam
Top tension member : 5/16" HDG steel cable
Ballast and bottom tension : 5/16" HDG steel chain
End connectors : ASTM F962-94 universal "Z" connector, fitted with stainless steel toggle pin and lanyard
Water holes : 24
Anchor points : 2
Weight per 100' section : 275 pounds
Storage volume per 100' section : 44 ft³
Boom ultimate tensile strength: 16000⁺pounds
Buoyancy to weight ratio : 6.62
Section length options : 50 ft / 100 ft

Boom Configuration
A: Top Tension Pocket
B: Top Tension
C: Cable eye with thimble
D: Shackle
E: ASTM End Connectors
F: One inch RF welds
G: Foam Log
H: Toggle Pin
I: Toggle Pin hole
J: Anchor Point
K: Air and water drainage hole
L: Chain Pocket
M: Ballast Chain



Texas Boom Company
 16600 Park Row Drive
 Houston, TX 77084
 (281) 441-2002
 sales@texasboom.com

Rev B: 4/16/2020